

COMPACT FUEL CELL FEED PROCESSING SYSTEM

[0001] The United States Government has rights in this invention pursuant to contract no. DE-AC05-00OR22725 between the United States Department of Energy and UT-Battelle, LLC.

FIELD OF THE INVENTION

[0002] The present invention relates to fuel cells, and more particularly to fuel cell feed processing systems wherein reformat gas comprising, primarily, hydrogen and water vapor is produced from a mixture of natural gas, gasoline, and/or other gaseous hydrocarbons with air using a carbon foam heat exchanger and carbon fiber composite molecular sieve scrubber instead of conventional desulfurizers, shift reactors, and partial oxidation reactors.

BACKGROUND OF THE INVENTION

[0003] Typical fuel reforming systems in use today decompose complex hydrocarbon fuel into simpler compounds including H_2 , CO_2 , H_2O , and CH_4 . Hydrocarbon fuels are fed into a fuel reformer of autothermal, steam, or microchannel type that catalyzes the fuel into a mixture called reformat. The reformat is passed through a desulfurizer to remove all sulfur bearing species in the gas stream. The reformat then goes through a shift reactor that reduces the CO to a few percent and raises the H_2 level by 10 to 12%. The final stages of the fuel processor consist of CO polishing, which eliminates all remnants of CO either by extraction or conversion to CO_2 in the partial oxidation reactor and cooling of the reformat in a heat exchanger. This current approach is not desirable for mobile or transportation equipment and most stationary applications because the apparatus required is large, complex, and expensive. For use in any of the low-temperature fuel cells the CO and CO_2 must be removed prior to the reformed gas entering the fuel cell. In the case of the polymer electrolyte membrane (PEM) fuel cell the CO is removed in a 3-stage process in which the gas undergoes a low-temperature and high-temperature water gas shift process in which the CO is converted to CO_2 in a partial oxidation reactor. In addition, the catalyst in the shift reactor is sensitive to small amounts of sulfur in the gas stream and therefore, any residual H_2S must be removed prior to entry into the shift reactor. Improvements in the

process that lead to a reduction in the mass or volume of apparatus and decrease in equipment or operating costs have long been desired.

OBJECTS OF THE INVENTION

[0004] Accordingly, objects of the present invention include an apparatus for an improved fuel cell feed processing system which is smaller and more energy-efficient than existing equipment. Reformate gas of hydrogen and water vapor is produced from a mixture of hydrocarbons and air using a carbon foam heat exchanger and carbon fiber composite molecular sieve scrubber and further methods for utilizing the apparatus to provide a gas stream composed of only H_2 and H_2O . Further and other objects of the present invention will become apparent from the description contained herein.

SUMMARY OF THE INVENTION

[0005] In accordance with one aspect of the present invention, the foregoing and other objects are achieved by a fuel cell feed processing system which comprises a fuel reformer of a type selected from the group consisting of autothermal type fuel reformers, steam type fuel reformers, and microchannel type fuel reformers for catalyzing fuel forming a gas mixture comprising H_2 , CO, CO_2 , and CH_4 called reformate, and further comprising a means for introducing fuel and air into the reformer; a heat exchanger, configured and communicably connected to the fuel reformer so that reformate from the fuel reformer is passed into and through the heat exchanger for cooling the reformate; and, a scrubber, configured and communicably connected to the heat exchanger so that the cooled reformate from the heat exchanger may be passed into and through the scrubber for removing CO, CO_2 , and H_2S from the cooled reformate, the scrubber further comprising a means for passing scrubbed reformate from the scrubber; the reformer, the heat exchanger, and the scrubber being communicably connected in series so that gaseous material may pass through the reformer, the heat exchanger and the scrubber sequentially.

[0006] In accordance with a second aspect of the present invention, a fuel cell feed processing system comprises a fuel reactor for catalyzing fuel forming a gas mixture called reformate

comprising essentially H_2 , CO , CO_2 , and H_2O , the fuel reactor further comprising means for introducing fuel and air into the fuel reactor; a heat exchanger, configured and communicably connected to the fuel reactor so that reformat from the fuel reactor is passed into and through the heat exchanger for cooling the reformat; a scrubber, configured and communicably connected to the heat exchanger so that the cooled reformat from the heat exchanger may be passed into and through the scrubber for extracting CO from the cooled reformat, the scrubber further comprising means for passing scrubbed reformat from the scrubber; and, a fuel reformer, configured and communicably connected to the scrubber so that CO isolated from the reformat in the scrubber is recycled into and through the fuel reformer for conversion to reformat, the fuel reformer being further configured and communicably connected to the heat exchanger so that reformat from the fuel reformer may be passed into and through the heat exchanger; the reactor, the heat exchanger, and the scrubber being communicably connected in series so that gaseous material may pass through the reformer, the heat exchanger, and the scrubber sequentially and the reformer connected in a parallel manner so that some material may pass from the scrubber into and through the fuel reformer and may further pass from the fuel reformer into and through the reactor at the same time material passes through the reactor, the heat exchanger, and the scrubber sequentially.

[0007] In accordance with a third aspect of the present invention, a fuel cell feed processing system comprises: a scrubber for removing sulfur bearing species from natural gas or LPG feed streams, a fuel reactor for catalyzing fuel forming a gas mixture called reformat comprising essentially H_2 , CO , CO_2 , H_2O , and trace amounts of CH_4 , said fuel reactor further comprising means for introducing fuel and air into said fuel reactor; a heat exchanger, configured and communicably connected to said fuel reactor so that reformat from said fuel reactor is passed into and through said heat exchanger for cooling the reformat; a scrubber, configured and communicably connected to said heat exchanger so that the cooled reformat from said heat exchanger may be passed into and through said scrubber for extracting CH_4 from the cooled reformat, said scrubber further comprising means for passing scrubbed reformat from said scrubber, and a fuel reformer configured and communicably connected to said scrubber so that CH_4 isolated from the reformat in said scrubber is recycled into and through said fuel reformer for conversion to reformat, said fuel reformer being further configured and communicably

connected to said heat exchanger so that reformat from the fuel reformer may be passed into and through said heat exchanger; said reactor, said heat exchanger, and said scrubber being communicably connected in series so that gaseous material may pass through said reformer, said heat exchanger, and said scrubber sequentially and said reformer connected in a parallel manner so that some material may pass from said scrubber into and through said fuel reformer and may further pass from said fuel reformer into and through said reactor at the same time material passes through said reactor, said heat exchanger, and said scrubber sequentially.

[0008] In accordance with a fourth aspect of the present invention, a fuel cell feed processing system comprises: a scrubber for removing sulfur bearing species from natural gas or LPG feed streams, a fuel reactor for catalyzing fuel forming a gas mixture called reformat comprising essentially H_2 , CO , CO_2 , H_2O , and trace amounts of CH_4 , said fuel reactor further comprising means for introducing fuel and air into said fuel reactor; a heat exchanger, configured and communicably connected to said fuel reactor so that reformat from said fuel reactor is passed into and through said heat exchange for cooling the reformat; a scrubber, configured and communicably connected to said heat exchanger so that the cooled reformat from said heat exchanger may be passed into and through said scrubber for extracting CO_2 from the cooled reformat, a pressure swing adsorption device for separating H_2 from the remaining gases,

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] Fig. 1 is a schematic drawing showing a conventional fuel processing or reforming system.

[0010] Fig. 2 is a schematic drawing showing a preferred embodiment of the compact fuel feed processing system of the present invention.

[0011] Fig. 3 is a schematic drawing showing an alternate embodiment of the compact fuel feed processing system of the present invention.

[0012] Fig. 4 is a schematic drawing showing another embodiment having pretreatment sulfur removal.

[0013] For a better understanding of the present invention, together with other and further objects, advantages and capabilities thereof, reference is made to the following disclosure and appended claims in connection with the above-described drawings.

DETAILED DESCRIPTION OF THE INVENTION

[0014] In a typical present-day fuel processing system as shown in Fig. 1, fuel such as natural gas or gasoline and air are fed into and through a fuel reformer 1, which may be of the autothermal, steam, or microchannel type, for catalyzing the fuel and forming a gas mixture comprising H_2 , CO, CO_2 , and small amounts of CH_4 , which is called reformat. The fuel reformer 1 is communicably connected to a desulfurizer 2 so that the reformat is passed into and through the desulfurizer 2 to remove essentially all sulfur bearing species in the reformat gas stream. The desulfurizer 2 is communicably connected to a shift reactor 3 so that the desulfurized reformat is passed into and through a shift reactor 3 to reduce the CO to a few percent and to raise the H_2 level by 10 to 12%. The shift reactor 3 is communicably connected to a partial oxidation reactor 4 so that the shift-reacted reformat is passed into and through the partial oxidation reactor 4 for CO polishing. The partial oxidation reactor 4 is communicably connected to a heat exchanger 5 so that the partially oxidized reformat is passed into and through the heat exchanger 5 for cooling the partially oxidized reformat. Elements 1, 2, 3, 4, and 5 are connected via piping in series so that gaseous material passes through elements 1, 2, 3, 4, and 5 sequentially. The cooled reformat can then be piped from heat exchanger 5 to and utilized in a fuel cell 6.




[0015] In a preferred embodiment of the present invention as shown in Fig. 2, the system shown in Fig. 1 is simplified as follows: The partial oxidation reactor 4 and shift reactor 3 have been removed and the desulfurizer 2 has been modified. In this embodiment, shown in Fig. 2, fuel such as natural gas or gasoline and air are fed into and through a fuel reformer 11, which may be of the autothermal, steam, or microchannel type, for catalyzing the fuel and forming a gas mixture comprising H_2 , CO, CO_2 , and small amounts of CH_4 , which is called reformat. The fuel reformer 11 is communicably connected to a heat exchanger 12 which, in a preferred embodiment, comprises graphite carbon foam (GCF), developed by the Oak Ridge National Laboratory in Oak Ridge, Tennessee, so that the reformat is passed into and through the heat exchanger 12 for cooling the

reformat. The graphite carbon foam material is further described in the following U.S. patents fully incorporated by reference herein: 6,033,506 issued March 7, 2000; 6,037,032 issued March 14, 2000; 6,387,343 issued May 14, 2002; and 6,261,485 issued July 17, 2001. The heat exchanger **12** is communicably connected to a scrubber **13** which, in a preferred embodiment, comprises carbon fiber composite molecular sieve material (CFCMS), developed by the Oak Ridge National Laboratory in Oak Ridge, Tennessee, so that the cooled reformat is passed into and through the scrubber **13** for removing essentially all CO, CO₂, and H₂S. The CFCMS material is further described in the following U.S. patents fully incorporated by reference herein: 5,827,355 issued October 27, 1998; 5,912,424 issued June 15, 1999; 5,925,168 issued July 20, 1999; 5,972,077 issued October 26, 1999, and 6,090,477 issued July 18, 2000. Elements **11**, **12**, and **13** are connected via piping in series so that gaseous material passes through elements **11**, **12**, and **13** sequentially. Optionally, CO and/or methane can be recycled from the scrubber **13** to the reformer **11** to further improve cycle efficiency. The scrubbed reformat can then be piped from scrubber **13** and utilized in a fuel cell **14**. In this embodiment, the resulting scrubbed reformat gas stream is composed essentially only of H₂ and H₂O. This embodiment provides a processing system that is smaller and more energy efficient than current-technology fuel processing systems. These advantages facilitate the use on on-board automotive and other transportation and portable applications.

[0016] In another embodiment of the present invention as shown in Fig. 3, the CFCMS material is used as a catalyst support for a catalytic reactor reformer **21**. Fuel such as CH₄ and water are fed into and through reactor **21** for catalyzing the fuel and forming a gas mixture called reformat. The reactor **21** is communicably connected to a graphitic foam heat exchanger **22**, which may be configured as a radiant cooler, so that the reformat, comprising essentially H₂, CO, CO₂, and H₂O, is passed into and through the heat exchanger **22** for cooling the reformat. The heat exchanger **22** is communicably connected to a CFCMS scrubber **23** which, in a preferred embodiment is a two-stage unit capable of isolating CO and/or methane by adsorption on a CFCMS variant activated to develop micropore characteristics, i.e., pore width, pore volume, and surface area, that provide specificity for CO and/or methane adsorption and, thus, removal from the gas stream, so that the cooled reformat is passed into and through the CFCMS scrubber **23** to extract CO and/or methane

from the reformat. The CFCMS scrubber is communicably connected to a conventional fuel reformer **24** so that CO and/or methane from the CFCMS scrubber **23** is recycled into and through the fuel reformer **24** for conversion to reformat. The fuel reformer **24** is further communicably connected to the cooler **22** so that the reformat from the fuel reformer **24** is passed into and through the heat exchanger **22**. Elements **21**, **22**, and **23** are connected via piping in series so that material passes through elements **21**, **22**, and **23** sequentially. Element **24** is connected in a recycle or parallel manner so that some material may pass from element **23** through element **24** and back to element **22** at the same time material is passed through elements **21**, **22**, and **23** sequentially.

[0017] The same CO and/or methane recycle concept can be applied in the conventional fuel processing system shown in Fig. 1 and the compact fuel processing system shown in Fig. 2. In either the embodiment of Fig. 1 or the embodiment of Fig. 2, a reformer may be employed to convert any hydrocarbon, or certain oxygen-containing derivatives of hydrocarbons (such as ethanol, for example), to a mixture, reformat, composed primarily of CO and H₂, with some diluents and/or contaminant gases such as CO₂, CH₄, and H₂S, depending on the purity of the primary fuel and the effectiveness of the reformer in the conversion. The pertinent reformer reactions are:



[0018] The process of removing sulfur compounds may be conducted, and the equipment therefor located, at a variety of locations. In one embodiment shown in Fig. 4, sulfur compounds can be removed from a stream of natural gas at or near the gas wellhead using a CFCMS pre-scrubber **15** activated to develop micropore characteristics, i.e., pore width, pore volume, and surface area, which provide specificity for sulfur compound adsorption. In other embodiments, sulfur compounds may be removed from a stream of fuel at or near a point of use of the fuel, including points along a fuel supply pipeline or at the final use point for the fuel.

[0019] While there have been shown and described what are at present considered the preferred embodiments of the invention, it will be obvious to those skilled in the art that various changes and modifications can be prepared therein without departing from the scope of the inventions defined by the appended claims.